



M PAC HE

STRAPPING MACHINE

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The semi-automatic strapping machine M-PAC HE is suitable for horizontally strapping of pallets or, for example, auction trolleys. The machine can be used for strapping relatively small amounts of pallets or carts per day.

Advantages

- Strapping up to 2210 mm in height
- For PP strap of 12 or 15.5 mm
- Up to 690 N strapping tension
- Closure with welding tongue
- Mobile, so it can be used anywhere
- Stepless adjustment of strapping head
- Remote control for operation of the machine

Options

- Battery for more flexibility



[< CLICK HERE FOR A VIDEO OF THE M PAC HE >](#)



Technical specifications	
Min. package size	Approx. 170 mm (H)
Strapping material	PP strap 12 or 15,5 mm
Strap coil	Core diameter: 200 mm Outer diameter: 420 mm Width: 190 mm
Strap tension	Max. 690 N
Heating time	Approx. 30 sec.
Sealing	Heat-seal
Supply voltage	230 V, 50 Hz or battery
Machine weight	Approx. 160 kg
Machine height	2830 mm

S.A. Cyklop Belgium N.V.
Boulevard International 55 C3
1070 Brussels

+32 2 7260080
www.cyklop.be
info@cyklop.be

